

Council Of Energy Resource Tribes

5670 So. Syracuse Circle
Suite 312 • Englewood, Colorado 80110
(303) 779-4760

Executive Committee:

Peter MacDonald Chairman Navaio

Floyd Correa Vice-Chairman Pueblo of Laguna

Leonard Atole Secretary Jicarilla Apache

Allen Rowland
Treasurer
Northern Cheyenne

Leonard Burch Executive Member Southern Ute

Forrest Horn
Executive Member
Crow

Wilfred Scott Executive Member Nez Perce

Board Members:

Acoma Pueblo
Blackfeet
Cheyenne River Sioux
Chippewa-Cree
Colville
Fort Belknap
Fort Berthold
Fort Hall
Fort Peck
Hopi

Senta Ana Pueblo Spokane Uintah-Ouray

Jemez Pueblo

Ute Mountain Wind River

Yakima Zia

Executive Director:

Ed Gabriel

June 11, 1979

Governor Floyd Correa Pueblo of Laguna Council Box 194 Laguna, NM 87026

Dear Governor Correa:

Confidential Claim Retracted

Authorized by:__

Date: 6/12/13

Pursuant to our meeting and your request of May 22, 1979, we have incorporated and consolidated the recommendations and stipulations of Kilborn/NUS, BIA and CERT, concerning the Anaconda Company's proposed push-back in the vicinity of Highway 279. Copies of the individual recommendations and stipulations are attached.

RECOMMENDATIONS & STIPULATIONS

- 1. We concur with the Council's decision to utilize open pit mining operations rather than underground mining operations.
- 2. We concur with the Council's decision in selecting alternate "B" for the rerouting of Highway 279. If, for reasons of lack of funding, alternate "B" is not constructed, alternate "A" should not automatically be accepted.
- 3. The sides of the final pit configuration (highwall) to be left at a slope which is safe, stable and modified enough to lessen erosion. It is felt that a ratio of l½ horizontal: I vertical would be adequate for these purposes. Benches will be permitted in the highwall, and are indeed recommended; the concern is for the overall slope of the highwall.
- 4. The pit should be backfilled with suitable material to at least four feet above the Jackpile Sandstone.
- 5. Interior backfill slopes should be as gentle as possible, 4 horizontal: 1 vertical or 5 horizontal: 1 vertical. This stipulation and item #3 above are guidelines, and must be reasonable enough so as not to endanger the economics of the proposed operation.



9384141

- 6. The bottom of the pit should be left relatively flat without any area left to accumulate ground water.
- All available and suitable "topsoil" in the area of the 7. proposed mine be stockpiled and eventually replaced on the backfill to a minimum depth of two feet. The remaining "topsoil" material could be used on other areas of the mine as reclamation proceeds,
- 8. Anaconda's reclamation plan should include the following information at a minimum
 - -an estimate of available topsoil
 - -storage location and/or placement depth of topsoil
 - -slope configurations and seedbed preparation
 - -seeding mixtures (species and rates)
 -use of containerized material

 - -use of mulch (type, application rate and method)
 - -fertilizer type and application rate
- 9. Native grass and shrub species should be used when the area is revegetated, and both CERT and the Superintendent at Southern Pueblos Agency should be consulted for other recommendations prior to rehabilitation.
- 10. The recommendation plan submitted by Anaconda should be viewed as flexible, allowing modifications based on advances in reclamation technology, if approved by the tribe.

If you have any questions or comments regarding the above recommendations and stipulations, please contact us.

Sincerely yours,

C. David White

C. David White Environmental Analyst

CDW:yr

cc: Ed Gabriel Sean Muller David Krebs Constance Brown Kenneth Payton

Attachment

RECEIVED

JUN 1 8 1979

PUEBLO OF LACTINA GOVERNOR'S OFFICE